

### Recommended P.C. Board Hole Layout

### Specifications

- Current Rating : 1 Amp
- Insulator Resistance : 1000 Megohms min.
- Contact Resistance : 20 m ohms max.
- Dielectric Withstanding : AC 300V
- Operating Temperature : -40°C ~ +105°C
- Contact Material : Brass
- Insulator Material : Polyester, UL 94V-0 Nylon-6T
- Contact Plated : See Option
- Standard: Full Gold Flash

### Order Information

BHC1 - S 0 XX - C 0 XX - X

Serial No. \_\_\_\_\_

Terminal Type \_\_\_\_\_

S : Straight Type

No. of Contact \_\_\_\_\_

Body Option \_\_\_\_\_

C:With Polarization Notch

Contact Plated \_\_\_\_\_

Insulator Option \_\_\_\_\_

N : Nylon-6T ( Standard)


L : LCP

Contact Plating Option	Full Gold Plating	Gold Plated On Contact Area Tin Plated On Solder Area	Full Tin Plating
GA : Gold Flash GC : Gold 10u" GD : Gold 15u" GE : Gold 30u"	SA : Gold Flash SC : Gold 10u" SD : Gold 15u" SE : Gold 30u"	TA : Tin 100u"	

GENERAL TOLERANCE	
X. ± 0.50	X. ° ± 5°
.X ± 0.20	.X ° ± 2°
.XX ± 0.10	.XX ° ± 1°
DATE:2011/01/12	SSV1

單位 (UNIT)	料號 (PART NO.)	檢驗 (CHECKED)	製圖 (DRAWN)
mm	BHC1-S0XX-00XX	Mary	Fen-Fen
Alice			

圖號 (DWG NO.)	比例 (SCALE)	張數 (SHEET)	頁次 (REV.)
BHC1-S0XX	4:1	1/1	A


**玆允企業有限公司**  
 IO PARTS Enterprise Co., Ltd.  
 Box Header P1.27 X 1.27mm  
 H:5.4mm Straight Type