

Specifications

Current Rating : 2 Amps
 Insulator Resistance : 1000 Megohms min.
 Contact Resistance : 20 m ohms max.
 Dielectric Withstanding : AC 500V
 Operating Temperature : -40°C ~ +105°C
 Contact Material : Brass
 Insulator Material : Polyester, UL 94V-0
 Standard : Nylon-6T
 Contact Plating : See Option / Standard: Full Gold

Order Information

BHB1 - R 0 XX - 00 XX

Serial No. _____
 Terminal Type _____
 R : Right Angle Type
 No. of Contacts _____
 Contact Plated _____


| Contact Plating | Full Gold Plating | Gold Plating On Contact Area Tin Plating On Solder Area | Full Tin Plating |
|-----------------|---|---|------------------|
| Option | GA : Gold Flash GC : Gold 10u" GD : Gold 15u" GE : Gold 30u" | SA : Gold Flash SC : Gold 10u" SD : Gold 15u" SE : Gold 30u" | TA : Tin 100u" |

| Pos. | Dimension | | | Pos. | Dimension | | |
|------|-----------|-------|-------|------|-----------|-------|-------|
| | A | B | C | | A | B | C |
| 06 | 13.20 | 12.10 | 4.00 | 30 | 37.20 | 36.10 | 28.00 |
| 08 | 15.20 | 14.10 | 6.00 | 32 | 39.20 | 38.10 | 30.00 |
| 10 | 17.20 | 16.10 | 8.00 | 34 | 41.20 | 40.10 | 32.00 |
| 12 | 19.20 | 18.10 | 10.00 | 36 | 43.20 | 42.10 | 34.00 |
| 14 | 21.20 | 20.10 | 12.00 | 40 | 47.20 | 46.10 | 38.00 |
| 16 | 23.20 | 22.10 | 14.00 | 44 | 51.20 | 50.10 | 42.00 |
| 18 | 25.20 | 24.10 | 16.00 | 50 | 57.20 | 56.10 | 48.00 |
| 20 | 27.20 | 26.10 | 18.00 | 60 | 67.20 | 66.10 | 58.00 |
| 22 | 29.20 | 28.10 | 20.00 | 64 | 71.20 | 70.10 | 62.00 |
| 24 | 31.20 | 30.10 | 22.00 | 68 | 75.20 | 74.10 | 66.00 |
| 26 | 33.20 | 32.10 | 24.00 | | | | |

| GENERAL TOLERANCE | | | |
|-------------------|-------------|--|--|
| X. ± 0.50 | X. ° ± 5° | | |
| .X ± 0.20 | .X ° ± 2° | | |
| .X X ± 0.10 | .X X ° ± 1° | | |
| Date:2009/12/17 | SSVZ | | |

| 單位 (UNIT) | 料號 (PART NO.) | 檢驗 (CHECKED) | 製圖 (DRAWN) |
|-----------|----------------|--------------|------------|
| mm | BHB1-R0XX-00XX | Mary | Fen-Fen |

| 圖號 (DWG NO.) | 比例 (SCALE) | 圖法 (PROJ.) | 張數 (SHEET) | 張次 (REV.) |
|--------------|------------|------------|------------|-----------|
| BHB1-R0XX | 2 : 1 | 第三角 | 1 / 1 | 1.0 |


益允企業有限公司
 IO PARTS Enterprise Co., Ltd.
 名稱 (TITLE): Box Header Pitch 2.0mm
 R/A Type