



Recommended P.C. Board Hole Layout

Material:
 Pin(outer sleeve): Brass,machined CuZn38Pb2
 Plating(outer sleeve):
 Tin plated:2um/80u" Ni, 5um/200u" Sn
 Gold Plated:2um/80u" Ni,Full gold
 Insulator(black): Glass filled UL94V-0

Electrical:
 Current rating: 3 Amps/Contact max.
 Contact resistance: ≤4mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Operating voltage: 60VAC/DC

Order Information

MICS - XX - 6 X T2 GA
 Serial No.: _____
 No. of Contacts: 24,28,32,40,48,50,52
 Bar Option
 0:Without Bar
 1:With Bar
 Pin Plating Option
 T2: Tin plating 200u"
 Clip Plating Option
 GA:Gold Flash



IC Socket Pitch:2.54mm
 Machine Pin / Footprint :0.6"

GENERAL TOLERANCE		單位 (UNIT)	料號 (PART NO.)	圖號 (DWG. NO.)
X. ± 0.50	X. ° ± 5°	mm	MICS-XX-6XXXXXX	MICS-XX-6XXXXXX
.X ± 0.20	.X ° ± 2°	mm	審核 (APPROVAL)	比例 (SCALE)
.XX ± 0.10	.XX ° ± 1°	Alice	Mary	3:1
DATE:2008/03/05	SMR		Fen-Fen	角法 (PROJ.)

